

Desempeño		Control de energía	
Carga rápida	✓	Voltaje de entrada AC	100 - 240 V
Tecnología Flicker free (reduce el parpadeo de la pantalla)	✓	Frecuencia de entrada AC	50/60 Hz
Tecnología Low Blue Light (baja luz azul)	✓	Tipo de fuente de alimentación	Interno
Multimedia		Escala de eficiencia energética	
Número de altavoces	2	De la A a la G	
Potencia estimada RMS	4 W	Peso y dimensiones	
Altavoces incorporados *	✓	Ancho del dispositivo (con soporte)	540 mm
Cámara incorporada *	✗	Profundidad dispositivo (con soporte)	200,1 mm
Diseño		Altura del dispositivo (con soporte)	502,9 mm
Posicionamiento de mercado *	Oficina	Peso (con soporte)	5,37 kg
Color del producto *	Negro	Ancho (sin base)	540 mm
Bisel frontal	Negro	Profundidad (sin base)	50,7 mm
Soporte desmontable	✓	Altura (sin base)	326,3 mm
Puertos e Interfaces		Peso (sin base)	3,66 kg
Conector USB incorporado *	✓	Empaquetado	
Versión de conector USB	3.2 Gen 1 (3.1 Gen 1)	Ancho del paquete	613 mm
Tipo de puerto USB de carga	USB Tipo C	Profundidad del paquete	162 mm
Número de puertos ascendentes	1	Altura del paquete	519 mm
Cantidad de puertos USB descendentes de tipo A	4	Peso del paquete	8,31 kg
USB Type-C DisplayPort Alternate Mode	✓	Longitud del cable USB	1,8 m
Suministro de potencia USB	✓	Contenido del embalaje	
Entrega de energía USB (USB Power Delivery) de hasta	65 W	Cables incluidos	Corriente alterna, HDMI, DisplayPort, USB Tipo C
HDMI *	✓	Longitud del cable DisplayPort	1,8 m
Número de puertos HDMI	1	Longitud del cable HDMI	1,8 m
Versión HDMI	1.4	Longitud del cable	1,8 m
Cantidad de DisplayPorts	1	Sostenibilidad	
Cantidad de salidas DisplayPort	1	Certificados de sostenibilidad	EPEAT Gold, TCO
Versión de DisplayPort	1.2	No contiene	Mercurio, PVC/BFR
Salida de audio	✓	Otras características	
Salida de auriculares *	✓	Compatibilidad	VESA-P2
Salidas para auriculares	1	Oscurecimiento local	✓
Auriculares	3,5 mm	Tipo de acabado exterior	Con relieve
Built-in conmutador KVM	✓	Libre de metales pesados	Hg (mercurio)
Conexión		Tipo de grosor del bisel embellecedor	Sin marco
Ethernet	✓	Periodo de garantía	3 año(s)
Ergonomía		Certificados de conformidad	CE
montaje VESA *	✓	Tiempo medio entre fallos	70000 h
		Certificación	WEEE,REACH compliant,RoHs compliant,HF,CB,TUV-GS-Mark,ISO 9241-307,EAC,FCC
		Datos de reciclado	
		Packaging recyclability rate	100%
		Product post-consumer recycled plastic	85%
		Packaging recycled content	100%



4038986140751

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.