



| Exhibición                                                  |                       | Control de energía                        |                                                                                                                                 |
|-------------------------------------------------------------|-----------------------|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Gama de colores estándar                                    | DCI-P3, sRGB          | Consumo de energía (SDR) por 1000 horas * | 45 kWh                                                                                                                          |
| Cobertura sRGB (típica)                                     | 100%                  | Consumo de energía (HDR) por 1000 horas * | 50 kWh                                                                                                                          |
| Gama de colores DCI-P3                                      | 99%                   | Consumo energético *                      | 32 W                                                                                                                            |
| Desempeño                                                   |                       | Consumo de energía (apagado)              | 0 W                                                                                                                             |
| NVIDIA G-SYNC *                                             | ✗                     | Consumo de energía (ahorro)               | 0,5 W                                                                                                                           |
| AMD FreeSync *                                              | ✗                     | Voltaje de entrada AC                     | 100 - 240 V                                                                                                                     |
| Compatibilidad con Adaptive Sync de VESA                    | ✓                     | Frecuencia de entrada AC                  | 50/60 Hz                                                                                                                        |
| Tecnología Flicker free (reduce el parpadeo de la pantalla) | ✓                     | Tipo de fuente de alimentación            | Interno                                                                                                                         |
| Tecnología Low Blue Light (baja luz azul)                   | ✓                     | Escala de eficiencia energética           | De la A a la G                                                                                                                  |
| Multimedia                                                  |                       | Peso y dimensiones                        |                                                                                                                                 |
| Número de altavoces                                         | 2                     | Ancho del dispositivo (con soporte)       | 610,3 mm                                                                                                                        |
| Potencia estimada RMS                                       | 4 W                   | Profundidad dispositivo (con soporte)     | 239,7 mm                                                                                                                        |
| Altavoces incorporados *                                    | ✓                     | Altura del dispositivo (con soporte)      | 584,9 mm                                                                                                                        |
| Cámara incorporada *                                        | ✗                     | Peso (con soporte)                        | 7,5 kg                                                                                                                          |
| Diseño                                                      |                       | Ancho (sin base)                          | 610,3 mm                                                                                                                        |
| Posicionamiento de mercado *                                | Diseño gráfico        | Profundidad (sin base)                    | 596 mm                                                                                                                          |
| Color del producto *                                        | Negro                 | Altura (sin base)                         | 378,8 mm                                                                                                                        |
| Soporte desmontable                                         | ✓                     | Peso (sin base)                           | 4,96 kg                                                                                                                         |
| Color de pies                                               | Negro                 | Empaquetado                               |                                                                                                                                 |
| Puertos e Interfaces                                        |                       | Ancho del paquete                         | 884 mm                                                                                                                          |
| Conector USB incorporado *                                  | ✓                     | Profundidad del paquete                   | 196 mm                                                                                                                          |
| Versión de conector USB                                     | 3.2 Gen 2 (3.1 Gen 2) | Altura del paquete                        | 685 mm                                                                                                                          |
| USB Type-C DisplayPort Alternate Mode                       | ✓                     | Peso del paquete                          | 15,1 kg                                                                                                                         |
| Suministro de potencia USB                                  | ✓                     | Tipo de embalaje                          | Caja                                                                                                                            |
| Entrega de energía USB (USB Power Delivery) de hasta        | 96 W                  | Contenido del embalaje                    |                                                                                                                                 |
| HDMI *                                                      | ✓                     | Stand incluido                            | ✓                                                                                                                               |
| Número de puertos HDMI                                      | 2                     | Otras características                     |                                                                                                                                 |
| Versión HDMI                                                | 2.1                   | Certificación                             | Mac Compliance FSC MIX Calman Ready VESA DisplayHDR 400 True Black TÜV Low Blue Light TÜV Flicker-free EPEAT Silver Energy Star |
| Cantidad de DisplayPorts                                    | 1                     |                                           |                                                                                                                                 |



4711636229470



0199291314245



199291314245

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.